



# SAFETY DATA SHEET

Revision Date 14-May-2020

Version 4

## 1. IDENTIFICATION

### Product identifier

**Product Name** 26MA POWERBEAD HIGH TEMP RED RTV SILICONE 7.25 OZ AE

### Other means of identification

**Product Code** 81915

### Recommended use of the chemical and restrictions on use

**Recommended Use** Sealant

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**E-mail address:** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Gases under pressure	Compressed gas

### Label elements

#### **Emergency Overview**

#### **Signal word**

**Warning**

Causes skin irritation  
Causes serious eye irritation  
Contains gas under pressure; may explode if heated



**Appearance** Red

**Physical state** Paste Liquid

**Odor** Acetic acid

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

Not applicable.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
AMORPHOUS SILICA	7631-86-9	7 - 13
ACETIC ACID	64-19-7	1 - 5

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice**

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

**Eye contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin contact**

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

**Inhalation**

Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

**Ingestion** Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.

**Self-protection of the first aider** Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** See section 2 for more information.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Keep victim warm and quiet.

**5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing media**

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO2, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

**Unsuitable extinguishing media**

None

**Specific hazards arising from the chemical**

Some may burn but none ignite readily. Ruptured cylinders may rocket.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not touch or walk through spilled material. Stop leak if you can do it without risk.

**Other Information** Ventilate the area.

**Environmental precautions**

**Environmental precautions** Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

**Methods and material for containment and cleaning up**

**Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

**Methods for cleaning up** Do not direct water at spill or source of leak.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling**

Contents under pressure. Do not puncture or incinerate cans. Avoid contact with skin and eyes. Wash thoroughly after handling. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Protect from moisture. Protect from sunlight. Store in a well-ventilated place. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

**Incompatible materials**

Strong oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
AMORPHOUS SILICA 7631-86-9	-	TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m <sup>3</sup> <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
ACETIC ACID 64-19-7	STEL: 15 ppm TWA: 10 ppm	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> (vacated) TWA: 10 ppm (vacated) TWA: 25 mg/m <sup>3</sup>	IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls**

Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Tight sealing safety goggles.

**Skin and body protection**

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations**

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Paste Liquid
<b>Appearance</b>	Red
<b>Odor</b>	Acetic acid
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
<b>Melting point / freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	No information available	Polymerization
<b>Flash point</b>	> 95 °C / > 203 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	<5 mm Hg	
<b>Vapor density</b>	>1	Air = 1
<b>Relative density</b>	1.05	
<b>Water solubility</b>	Not applicable	Polymerization
<b>Solubility(ies)</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	1
<b>Density</b>	No information available
<b>Bulk density</b>	No information available
<b>SADT (self-accelerating decomposition temperature)</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**

No information available

**Chemical stability**

Stable under normal conditions

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides  
Nitrogen oxides (NOx)  
Acetic acid  
Oxides of sulfur  
Formaldehyde

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
ACETIC ACID 64-19-7	= 3310 mg/kg ( Rat )	= 1060 mg/kg ( Rabbit )	= 11.4 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
AMORPHOUS SILICA 7631-86-9	-	Group 3	Known	X

IARC (International Agency for Research on Cancer)  
*Group 2B - Possibly Carcinogenic to Humans*  
*Not classifiable as a human carcinogen*  
 NTP (National Toxicology Program)  
*Known - Known Carcinogen*  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
*X - Present*

**Target Organ Effects** Eyes, Respiratory system, Skin, Teeth.

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 26925 mg/kg  
**ATEmix (dermal)** 15654 mg/kg

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility

No information available.

Chemical Name	Partition coefficient
ACETIC ACID 64-19-7	-0.31

**Other adverse effects**  
 No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETIC ACID 64-19-7	Toxic Corrosive Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID No** 1950  
**Ethanol** Aerosols, Limited Quantity (LQ)  
**Hazard Class** 2.2  
**Emergency Response Guide Number** 126

**IATA**

**UN/ID No** ID 8000  
**Ethanol** Consumer commodity  
**Hazard Class** 9  
**ERG Code** 9L

**IMDG**

**UN/ID No** 1950  
**Ethanol** Aerosols, Limited Quantity (LQ)  
**Hazard Class** 2.2  
**EmS-No** F-D, S-U

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Not determined  
**ENCS** Not determined  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Not determined

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	No
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ACETIC ACID 64-19-7	5000 lb	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETIC ACID 64-19-7	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
AMORPHOUS SILICA 7631-86-9	*Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
NITROGEN 7727-37-9	X	X	X
ACETIC ACID 64-19-7	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

Non-controlled

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 1	<b>Flammability</b> 1	<b>Instability</b> 0	-
<b>HMIS</b>	<b>Health hazards</b> 1	<b>Flammability</b> 1	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)



HMIS (Hazardous Material Information System)

**Revision Date** 14-May-2020

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**