



SAFETY DATA SHEET

Revision Date 09-Mar-2016

Version 2

1. IDENTIFICATION

Product identifier

Product Name PC 80BR YELLOW SUPER WEATHERSTRIP ADHESIVE 59ML

Other means of identification

Product Code 80539

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Contact adhesive

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number

1-87-Permatex
(877) 376-2839

24 Hour Emergency Phone Number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address

mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Causes skin irritation
Causes serious eye irritation
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure

Highly flammable liquid and vapor



Appearance Yellow

Physical state Viscous liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Take precautionary measures against static discharge
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity 31 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
METHYL ETHYL KETONE (BUTANONE)	78-93-3	10 - 30	*
ACETONE	67-64-1	10 - 30	*
TOLUENE	108-88-3	10 - 30	*

N-HEXANE	110-54-3	10 - 30	*
----------	----------	---------	---

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Highly flammable. Keep product and empty container away from heat and sources of ignition. Vapors may travel to source of ignition and flash back.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Remove all sources of ignition. When using do not eat, drink or smoke.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store locked up.

Incompatible materials Strong oxidizing agents, Acids, Bases

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ETHYL KETONE (BUTANONE) 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
N-HEXANE 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Viscous liquid
Appearance Yellow
Odor Solvent
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	55 °C / 131 °F	
Flash point	-26 °C / -15 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	13.0%	
Lower flammability limit:	1.2%	
Vapor pressure	233 hPa @ 20°C (175 mmHg)	
Vapor density	>1	Air = 1
Relative density	0.889	
Water solubility	Immiscible in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	240°C (464°F)	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point No information available
Molecular weight No information available
VOC Content (%) 50%
Density No information available
Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids, Bases

Hazardous Decomposition Products

Carbon oxides
Nitrogen oxides (NOx)
Hydrogen chloride

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

- Inhalation** May be harmful if inhaled. May cause drowsiness or dizziness.
- Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
- Skin contact** May cause skin irritation and/or dermatitis.
- Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL ETHYL KETONE (BUTANONE) 78-93-3	= 2483 mg/kg (Rat) = 2737 mg/kg (Rat)	= 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
N-HEXANE 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Sensitization** No information available.
- Germ cell mutagenicity** No information available.
- Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)
Not classifiable as a human carcinogen*

- Chronic toxicity** May cause adverse liver effects.
- Target Organ Effects** Central nervous system, Eyes, kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3902 mg/kg
ATEmix (dermal)	6809 mg/kg
ATEmix (inhalation-dust/mist)	47 mg/l
ATEmix (inhalation-vapor)	35633 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

31 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	520: 48 h Daphnia magna mg/L EC50 5091: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static
ACETONE 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
TOLUENE 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
N-HEXANE 110-54-3	-	2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
METHYL ETHYL KETONE (BUTANONE) 78-93-3	0.29
ACETONE 67-64-1	-0.24
TOLUENE 108-88-3	2.65

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE (BUTANONE) 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159
ACETONE 67-64-1	-	Included in waste stream: F039	-	U002
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL ETHYL KETONE (BUTANONE) 78-93-3	Toxic Ignitable
ACETONE 67-64-1	Ignitable
TOLUENE 108-88-3	Toxic Ignitable
N-HEXANE 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no 1133
 Proper shipping name: Adhesives, Limited Quantity (LQ)
 Hazard Class 3
 Packing Group II
 Emergency Response Guide Number 128

IATA

UN/ID no ID 8000
 Proper shipping name: Consumer commodity
 Hazard Class 9
 ERG Code 9L

IMDG

UN/ID no 1133
 Proper shipping name: Adhesives, Limited Quantity (LQ)
 Hazard Class 3
 Packing Group II
 EmS-No F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 ENCS Complies
 IECSC Complies
 KECL Complies
 PICCS Complies
 AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	1.0
N-HEXANE - 110-54-3	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
 Chronic Health Hazard No
 Fire hazard Yes
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL ETHYL KETONE (BUTANONE) 78-93-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1 lb	-	RQ 1 lb final RQ RQ 0.454 kg final RQ
N-HEXANE 110-54-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TOLUENE - 108-88-3	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
METHYL ETHYL KETONE (BUTANONE) 78-93-3	X	X	X
TOLUENE 108-88-3	X	X	X
N-HEXANE 110-54-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 09-Mar-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet