



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Spray Nine® Concrete Cleaner

Revised 7/9/18

PRODUCT DESCRIPTION

Spray Nine® Concrete Cleaner is a powerful alkaline concrete cleaner formulated to cut through heavy deposits and lift away grease, grime and heavy ground-in dirt. It is ideal for garages, workshops, driveways, and walkways. Safe for use on traditional concrete surfaces, brick, stone, masonry, asphalt, slate and sealed patterned/ stained concrete surfaces.

PRODUCT BENEFITS

- Powerful cleaner for removing oil and grease from concrete floors
- High sudsing properties
- Non-clogging
- Economical to use
- Easy clean-up with water

TYPICAL APPLICATIONS

Applications

Garages
Service Stations
Machine Shops
Problem grease/oil areas

DIRECTIONS FOR USE:

Always wear protective clothing to prevent eye and skin contact.

For raw non-sealed and non-stained concrete:

Always test product in an inconspicuous area.

1. Loosen and remove any thick build-up of grease, oil and dirt. 2. Wet area with water. Floor must be wet but without puddles. 3. Sprinkle an even amount of cleaner over wet area. 4. Allow 5 minutes of contact time but DO NOT allow floor to dry. 5. Scrub area with a stiff broom or brush until stains dissolve. 6. Rinse area thoroughly and rinse any residue completely down driveway.

For sealed or decorative stained concrete:

Always test product in an inconspicuous area.

1. Prewash area with water to loosen and remove any build-up of debris, grease and dirt.
2. Dilute: 2oz of Spray Nine Garage Floor Cleaner in a 5-gallon (20 liter) bucket. 3. Wet area to be cleaned, floor should be wet but without

puddles. 4. With a stiff broom, mop diluted product onto area to be cleaned and scrub until stains dissolve. Do not let product sit or dry. 5. Rinse area thoroughly right away and rinse any residue completely down driveway.

NOTE: PAINTED AND STAINED CONCRETE MUST BE PREVIOUSLY SEALED WITH A POLYURETHANE OR EPOXY FINISH. ALWAYS RINSE THOROUGHLY, RESIDUE MAY STAIN. AVOID PRODUCT CONTACT WITH WINDOWS, MIRRORS AND SOFT METALS (ALUMINUM).

PROPERTIES OF MATERIAL

Chemical Type	Alkaline Cleaner
Appearance	Yellow powder
Odor	Pine
Flash Point TCC F(C)	None
pH- 1% solution	~12.5

GENERAL INFORMATION

For safe handling information on this product, consult the product Safety Data Sheet, (SDS).

ORDERING INFORMATION

Part Number	Container Size
15701	1 Kg. Container

STORAGE AND DISPOSAL

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Keep product away from children. Rinse empty container thoroughly before discarding in trash or recycling container where available.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.