



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Weatherstrip Cement

INDUSTRIAL

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Weatherstrip Cement is a translucent rubber cement that seals rubber and serves to adhere weatherstripping.

PRODUCT BENEFITS

- Seals in minutes
- Dries to a tough, strong bond
- Easy to use

TYPICAL APPLICATIONS

- Door weatherstripping
- Windshield weatherstripping

DIRECTIONS FOR USE

1. Surfaces to be bonded must be clean, dry and free of oil and grease.
2. Apply an even coat of Weatherstrip Cement to the solid surface. Allow to dry.
3. Apply a liberal coat to weatherstripping. Set firmly in place.
4. Apply pressure on the bonded surface for a few minutes.
5. Allow to dry.

PROPERTIES OF UNCURED MATERIAL

	Typical Value
Chemical Type	Synthetic rubber
Appearance	Translucent
Odor	Solvent
Specific Gravity	0.73
Viscosity	Flow similar to honey
Flash Point, TCC, _F	-10

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as an adhesive for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80328 (DCD-19)	2 oz. tube, carded

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX) Revised 09/02